




HAYWARD®


Pool Fittings and Drains

Drains, Frames & Grates

COMMERCIAL ABS MAIN DRAIN

A full size, non-corrosive and non-conductive main drain sump, offering maximum piping versatility and economy.




MODEL NO.	SIZE	DESCRIPTION
SP-1062	3" Skt.	ABS Body, 9" x 9" Square Frame and Grate, Welded PVC Side Outlet Coupling, plus 2" Bottom connections with plugs.

Open Area — 44 sq. in.

HYDROSTATIC RELIEF VALVES



Spring loaded, leakproof self-cleaning O-ring seal. Non-corrosive, non-conductive.



MODEL NUMBER	PIPE SIZE	DESCRIPTION
SP-1056	1 1/2" MIP	Hydrostatic Relief Valve, ABS (White).
SP-1057	2" MIP	

SQUARE FRAMES & GRATES

Beautifully designed, generous open areas and deep vertical ribs for extra strength. Totally non-corrosive and non-conductive.





9", 12" and 18"

MODEL NO.	SIZE	DIM. A	DIM. B	SECURING SCREWS	OPEN AREA
SP-1031	9" x 9"	8-15/16"	10-1/2"	4	42 sq. in.
SP-1032	12" x 12"	11-15/16"	13-1/8"	4	68 sq. in.
SP-1033*	18" x 18"	17-3/4"	19-3/8"	8	168 sq. in.

*Four compartment, heavily Ribbed Frame receives Four (4) 9" x 9" Grates.


MAIN DRAIN COLLECTOR TUBE



SP-1055
1 1/2" Collector Tube.
For Hydrostatic Relief Valve.


ANTI-VORTEX COVER & FRAME

FOR CONCRETE POOLS




SP-1030AV

7-7/8" Diam., Frame and Cover, White, with securing screws.



Open Area — 7 sq. in.

ROUND FRAMES & GRATES



Open Area — 13 sq. in.



SP-1030

7 7/8" Diam., White, with securing screws.
Available on special order only.

DIRECTIONAL FLOW INLET FITTINGS



HYDRO-SWEEP
SP-1419-A

1 1/2" MIP
Fully adjustable to direct flow to any area of pool, giving proper circulation pattern.



HYDRO-STREAM
SP-1419-B, C, D, E



SP-1420
w/Rubber Director Nozzle

FLUSH PLUG

SP-1022-B



1 1/2" Plug, White, with gasket.

ALL-PURPOSE PLUG

SP-1022-C



1 1/2" All-Purpose Plug, White, with O-ring.

OUTLET FITTING GRATE INSERT

SP-1026 1 1/2" MIP, Installs in any 1 1/2" FIP wall outlet.




WALL INLETS

ADJUSTABLE and NON-ADJUSTABLE




White Body and Grate.



MODEL NO.	DESCRIPTION
SP-1423	Non-Adj.
SP-1423S	
SP-1424	Adj.
SP-1424S	

SP-1424 provides full range of flow adjustments, line testing and winterizing. Internal spinner valve disc is adjustable thru center hole in grate. SP-1423, non-adjustable fitting, is same as SP-1424 except furnished without internal spinner valve. SP-1423 is also ideally suited for use as a deck drain.



FLOOR INLET



FULLY ADJUSTABLE



White Body and Flush Diffuser Plate.

MODEL NO.	DESCRIPTION
SP-1425	1 1/2" FIP x 2" MIP
SP-1425S	1 1/2" Skt. x 2" MIP

Installs in pool floor to provide uniform, efficient, high velocity 360° distribution of water. Top diffuser plate is stationary and automatically provides proper flow angle away from floor to prevent staining or erosion. A full range of tamperproof flow settings, plus line testing and winterizing, is achieved by means of an internal spinner valve disc and O-ring seal.



GUTTER DRAIN

ATTRACTIVE and STREAMLINED

MODEL NO.	DESCRIPTION
SP-1019	2" FIP plus 2" Socket Connection. White Body and Grate.